

High Density Shielding Cable



RG-59/U Coaxial Cable (95% Shield Coverage, Standard Construction)

High density shielding cable specially designed and manufactured under the USA and Japanese Standard

Applications and Usage

- Best suited for CCTV installation
- CATV/MATV
- Satellite TVRO/Internet
- Telecomm Interconnect



RG-59/U Cable Construction

These series of coaxial cable are specially designed and manufactured to be use in the noisy area (high interference) and longer run system design. They are the most suited to CCTV system where the signal interruption degrading the system is not acceptable. The high density shielding (>95% coverage) of the cable clears up EMI/RF interference, especially, in 0 – 50 MHz frequency region which mostly affected by, for example, the transient signal generated by the motor starts up, electrical appliance emission and other sources leading the interference to the system. Moreover, they are also suitable to use in the CATV, MATV, Satellite TVRO/Internet and Telecomm

interconnect system. The signal attenuation meets the standard ensuring that it will fall under the designed margin of the power budget.

Product Highlights

- High density shielding (95% coverage) to protect the intervention of interference signal entering the cable/system.
- Standard signal attenuation
- Don't waste the time for cable reinstallation (save both time and unexpected expenses)

Physical Construction

Product Code	: PA59U95CBV
Conductor	: Ø0.80 MM Bare Copper
Insulation	: Ø3.65 MM FPE
Shielding	: Ø0.12 x 7 x 16 Bare Copper Wire Braid
% of Shield Coverage	: 95%
Jacket	: Ø6.20 MM High Quality PVC (70C)

Electrical Specifications

Impedance	: 75 ± 3 Ω
-----------	------------

Nominal Attenuation (dB/100M)

<u>Frequency (MHz)</u>	<u>Attenuation</u>
50	6.10
100	8.42
200	11.72
400	16.77
700	22.53
900	25.61
1000	26.98

Other special requirements, please note

Packing Information

Length	: 300M, 500M/Spool
	: 100M, 200M/Coil

SUVANITJIT LIMITED PARTNERSHIP

22/40 Moo 6 Soi Watkumpang, Rama II Road, Sameredum, Bangkhuntien BANGKOK 10150

Tel: 02-4151126, 02-8984215 Fax: 02-4151126 Mobile: 01-7722376

Note: The specifications are subjected to change without prior notice.

CCTV Cable RG-59U PA5995CBV Spec Sheet.doc